

KIDDE

G X 2 0 / F M - 2 0 0 ®

Fire Extinguishing System



I N T R O D U C T I O N

Halon fire extinguishants were regarded for many years as the most effective fire suppressants for a wide range of applications. Amendments to the Montreal Protocol of 1987 focused on the manufacture of Halons, however, and their production has now ceased in recognition of their virulent destruction of the ozone layer. In addition, new European legislation requires that Halon systems within the EU must be removed by the end of 2003.

As a result, recent years have seen a substantial reappraisal of approaches to fire protection. Kidde Fire Protection is at the forefront of new technologies in fire safety, offering a range of state-of-the-art fire extinguishing systems.

Kidde Fire Protection offers GX-20 systems containing FM-200®, a gaseous agent manufactured by Great Lakes Chemical Corporation, which has emerged as a viable alternative to the Halons on the basis of extensive trials. FM-200® is fast and effective with a low space/weight characteristic which is also environmentally-acceptable and safe for human exposure.

FM-200® has been adopted by the majority of the world's fire protection companies and is the most widely used Halon replacement, with tens of thousands of systems installed across the globe.

A S S E T P R O T E C T I O N

It is a chilling statistic that of companies suffering an accidental fire event, 43% never re-open and a further 29% close within three years. Ensure that your business is adequately protected and does not yield to this fate.


B E N E F I T S

- Fast and effective against a wide range of Class A, B and electrical fires
- Safe for occupied areas
- Non-corrosive and electrically non-conductive
- No post-discharge residue and clean-up
- Environmentally-acceptable
- 25 bar system
- Engineered and pre-engineered systems available
- Range of system release options
- Low installation and maintenance costs
- Computer design maximises effectiveness of system
- FMRC/LPCB approved components with ULI listed systems available on request
- Marine systems available

KIDDE

GX20 / FM-200®

Fire Extinguishing System



WHAT IS FM-200®?

FM-200® is a colourless, odourless gas containing only carbon, hydrogen and fluorine, thereby lacking the ozone-depleting presence of bromine atoms. Highly penetrative and achieving an homogeneous dispersion in the hazard zone, it acts on fires largely by physical means, lowering the temperature of the flame and fuel to a point at which combustion reactions cannot be sustained. There is no significant obscuration on discharge and this non-corrosive and electrically non-conductive agent causes no damage to sensitive equipment with no post-discharge clean-up required.

SAFETY TO PERSONNEL

A significant body of toxicity data has been obtained for FM-200® from over 70 studies. The US Environmental Protection Agency and the UK Halon Alternatives Group accepts the use of FM-200® in occupied spaces up to 9% concentration without mandated egress times and at up to 10.5% with mandated evacuation times. Since the agent does not act by oxygen-depletion in the hazard zone, it poses no human asphyxiation threat.

THE ENVIRONMENT

FM-200® has a zero ozone-depletion potential and a short atmospheric lifetime. When used in a fire event, FM-200® mitigates the effects of an uncontrolled fire and at the end of the lifetime of the system, the gas can be readily recovered and recycled.

SYSTEM DESIGN

The GX-20 range comprises a versatile line of cylinders, valves and related components which have been selected for use with FM-200® and have been subject to stringent testing procedures. Flexibility, quality and reliability make the Kidde Fire Protection GX-20 range the world's finest in fire safety and the equipment carries third party listing through the Factory Mutual Research Corporation and the Loss Prevention Certification Board. Systems are UL1058A compliant.

Both engineered and pre-engineered systems are available. The pre-engineered systems offer a low engineering/design cost option with defined maximum design parameters. Engineered systems offer optimum designs for the defined risks with reduced pipe sizes, unbalanced flows and common room and void protection possible.

KIDDE

GX20 / FM-200®

Fire Extinguishing System

GX - 20 CYLINDERS

A wide range of sizes is available, offering a choice of fill capacities to meet specific requirements and ensure maximum economy in installation. Each cylinder is manufactured from high strength alloy steel

The larger cylinders have an optional liquid level device for ease of contents monitoring and improved system maintenance.

GX - 20 VALVES

GX-20 valves are designed for optimum system performance, reducing pipe sizes and lowering installation costs. The fast-opening valves are available in a range of sizes and are manufactured from tough, corrosion-resistant brass under stringent quality control standards.

The valve design enables the Kidde worldwide network of factory-trained distributors to recharge the cylinders without the need for replacement parts. An easy-to-read gauge on the valve permits the convenient visual inspection of the cylinder pressure.

GX-20 valves are actuated by one of the following means:

- Electric solenoid
- Pneumatic
- Local manual release at the control head
- Manual release at a remote pull box

All related components from discharge nozzles to control heads are designed to be compatible, allowing a complete system to be configured using FMRC and LPCB approved Kidde Fire Protection equipment.

NOZZLES

A range of custom-designed nozzles is available including 180° wall-mounted and 360° ceiling-mounted types.

SYSTEM SPACE REQUIREMENTS

System space and weight are usually at a premium in industrial and commercial premises. FM-200® is stored as a liquid in nitrogen-pressurised containers at 25 bar, leading to minimal storage requirements comparing favourably with all other viable gaseous agents.

APPROVALS

Kidde FM-200 systems are FM listed, meet the criteria of UL1058A and carry LPCB design manual and component approval.

KIDDE

GX20 / FM - 200[®]

Fire Extinguishing System

APPLICATIONS

GX-20 systems are ideally suited to the protection of high value assets from both loss by fire damage and the accompanying catastrophic plant down-time. Applications include:

- Computer suites, EDP facilities and telecommunications hardware
- Control rooms such as railway signalling centres and air traffic management centres
- Stores and archives
- Heritage sites such as art galleries and museums
- Medical and laboratory equipment
- Petrochemical plant, offshore oil and gas installations, pipeline pumping stations
- Ship machinery spaces, rail locomotives and rolling stock

ASSURED RELIABILITY

Kidde Fire Protection systems are designed to conform to NFPA 2001 and BFPSA Code of Practice requirements. An empirically-verified windows-based computer program is used to model two-phase agent flow and ensure that the correct concentration of agent is achieved within 10 seconds throughout the protected zones as required by the NFPA Standard and BFPSA Code.

THE COMPANY

Backed by the worldwide technical and financial strength of Kidde International, Kidde Fire Protection offers a total capability approach to fire and explosion detection and suppression with over 60 years experience in the manufacture, design and commissioning of fire protection systems. The company has UK manufacturing facilities in Northolt, West London and Cramlington, Northumberland with Quality Assurance to BS EN ISO 9001.



ISO 9001
FM11925

THE COMPANY

Backed by the technical and financial strength of Kidde International, Kidde Fire Protection has over sixty years experience in designing, manufacturing and commissioning industrial and commercial fire protection systems throughout the world.

FURTHER INFORMATION

Contact your local Kidde distributor or

Kidde Fire Protection on +44 (0)1844 265003

for further information.

Kidde Fire Protection
UK Sales Office – Head Office

Thame Park Road, Thame,
Oxfordshire OX9 3RT, UK
Tel: +44 (0)1844 265003
Fax: +44 (0)1844 256156
E-mail: info@kfp.co.uk
Web: www.kfp.co.uk

UK Sales Office
Unit 12, Atley Way, North Nelson
Industrial Estate, Cramlington,
Northumberland
NE23 1WA UK.

Tel: +44 (0)1670 713455
Fax: +44 (0)1670 735553

International Offices
Dubai:

Tel: +971 4 337 2498
Fax: +971 4 337 5088

Hong Kong:
Tel: +852 2195 3688
Fax: +852 2743 7477

Singapore:
Tel: +65 424 7979
Fax: +65 424 7978

Australia:
Tel: +61 3 9765 3850
Fax: +61 3 9765 3800